

SEMINOLE TRIBE OF FLORIDA TRIBAL INSPECTOR' DEPARTMENT

6363 TAFT ST. SUITE 308 HOLLYWOOD, FL. 33024 OFFICE: (954) 894-1080 FAX: (954) 989-1571 EMAIL: <u>BUILDINGDEPT@SEMTRIBE.COM</u>

PERMIT APPLICATION/ MANUFACTURED HOME INSTALLATION

Applicant: Name of Licensed Dealer/Installer: License Number:	Permit #:				
Manufacturer's Name: Roof Zone: Number of Sections: Wind Zone: Wind Zone: Number of Sections: Wind Zone: Number of Sections: Wind Zone: Number of Sections: Wind Zone: Wind Zone: Wind Zone: Number of Sections: Wind Zone: Secilar # Secilar # Jecalar # Jec	Applicant: Name of Licensed Dealer/Installer:				
Manufacturer's Name: Roof Zone: Number of Sections: Wind Zone: Wind Zone: Number of Sections: Wind Zone: Number of Sections: Wind Zone: Number of Sections: Wind Zone: Wind Zone: Wind Zone: Number of Sections: Wind Zone: Secilar # Secilar # Jecalar # Jec	Address: License Number:				
SITE PREPARATION: Debris and Organic Material Removal: Compacted Fill: Water Drainage: Natural: Swale: Pad: Other: Pad: Other: Pad: Other: Other: Pad: Pad: Other: Pad:		Installation	Decal #:		
SITE PREPARATION: Debris and Organic Material Removal: Compacted Fill: Water Drainage: Natural: Swale: Pad: Other: Pad: Other: Pad: Other: Other: Pad: Pad: Other: Pad:					
SITE PREPARATION: Debris and Organic Material Removal: Compacted Fill: Water Drainage: Natural: Swale: Pad: Other: Pad: Other: Pad: Other: Other: Pad: Pad: Other: Pad:	Manufacturer's Name:				
SITE PREPARATION: Debris and Organic Material Removal: Compacted Fill: Water Drainage: Natural: Swale: Pad: Other: Pad: Other: Pad: Other: Other: Pad: Pad: Other: Pad:	Roof Zone:	Wind Zone			
SITE PREPARATION: Debris and Organic Material Removal: Compacted Fill: Water Drainage: Natural: Swale: Pad: Other: Pad: Other: Pad: Other: Other: Pad: Pad: Other: Pad:	Number of Sections: WID7	.`H LENGTH	I YEAR _	SERIAL #	
Debris and Organic Material Removal: Compacted Fill: Water Drainage: Natural: Swale: Pad: Other: Other: FOUNDATION: Load Bearing Soil Capacity: or Assumed 1000 PSF	Installation Standard Used: (Check O	ne) MANUFACTUREI	R'S MANUAL	15C-1	
Debris and Organic Material Removal: Compacted Fill: Water Drainage: Natural: Swale: Pad: Other: Other:	SITE PREPARATION:				
FOUNDATION: Load Bearing Soil Capacity: or Assumed 1000 PSF Footing Type: Pound in Place: Portable: Size and Thickness: I-Beam or Main Rail Piers: Single Tiered: Double Interlocked: Size of Piers: Placement O/C: Placement O/C: Placement Blocking Size: Placement O/C: Ridge Beam Support Blocking Size: Number: Location(s)	SHE I KEI AKATION.				
FOUNDATION: Load Bearing Soil Capacity: or Assumed 1000 PSF Footing Type: Pound in Place: Portable: Size and Thickness: I-Beam or Main Rail Piers: Single Tiered: Double Interlocked: Size of Piers: Placement O/C: Primeter Pier Blocking Size: Placement O/C: Ridge Beam Support Blocking Size: Number: Location(s)	Debris and Organic Material Remova	l: Compacte	d Fill:		
FOUNDATION: Load Bearing Soil Capacity: or Assumed 1000 PSF Footing Type: Pound in Place: Portable: Size and Thickness: I-Beam or Main Rail Piers: Single Tiered: Double Interlocked: Size of Piers: Placement O/C: Primeter Pier Blocking Size: Placement O/C: Ridge Beam Support Blocking Size: Number: Location(s)	Water Drainage: Natural:S	wale: Pad: _	Other:		
Load Bearing Soil Capacity: or Assumed 1000 PSF Footing Type: Pound in Place: Portable: Size and Thickness: I-Beam or Main Rail Piers: Single Tiered: Double Interlocked: Size of Piers: Placement O/C: Perimeter Pier Blocking Size: Placement O/C: Ridge Beam Support Blocking Size: Number: Location(s) Ridge Beam Support Footer Size: Number: Location(s) Ridge Beam Support Footer Size: Number: Location(s) Center Line Blocking: Number: Size: Location(s) Special Pier Blocking: Required: (Fireplace, Bay Window, Etc.) YES: NO: Matting of Multiple Units: Matting Gasket: Type Used: Spacing: O/C					
Footing Type: Pound in Place: Portable: Size and Thickness: I-Beam or Main Rail Piers: Single Tiered: Double Interlocked: Size of Piers: Placement O/C: Perimeter Pier Blocking Size: Placement O/C: Ridge Beam Support Blocking Size: Number: Location(s) Ridge Beam Support Footer Size: Number: Location(s) Center Line Blocking: Number: Size: Location(s) Special Pier Blocking: Required: (Fireplace, Bay Window, Etc.) YES: NO: Matting of Multiple Units: Matting Gasket: Type Used: Fasteners: ROOFS Type and Size: Spacing: O/C END WALLS Type and Size: Spacing: O/C FLOORS Type and Size: Spacing: O/C ANCHORS: Type 3150 Working Load: 4000 Working Load: Pleight of Unit: (Top of Foundation or Footer to Bottom of Frame) Number of Frame Ties: Spacing: O/C Angle of Strap: Degrees: Number of Sidewall Anchors: Zone II Zone III Number of Centerline Anchors: Number of Stabilizer Devices: Sumber of Stabilizer Device	FOUNDATION:				
Footing Type: Pound in Place: Portable: Size and Thickness: I-Beam or Main Rail Piers: Single Tiered: Double Interlocked: Size of Piers: Placement O/C: Perimeter Pier Blocking Size: Placement O/C: Ridge Beam Support Blocking Size: Number: Location(s) Ridge Beam Support Footer Size: Number: Location(s) Center Line Blocking: Number: Size: Location(s) Special Pier Blocking: Required: (Fireplace, Bay Window, Etc.) YES: NO: Matting of Multiple Units: Matting Gasket: Type Used: Fasteners: ROOFS Type and Size: Spacing: O/C END WALLS Type and Size: Spacing: O/C FLOORS Type and Size: Spacing: O/C ANCHORS: Type 3150 Working Load: 4000 Working Load: Pleight of Unit: (Top of Foundation or Footer to Bottom of Frame) Number of Frame Ties: Spacing: O/C Angle of Strap: Degrees: Number of Sidewall Anchors: Zone II Zone III Number of Centerline Anchors: Number of Stabilizer Devices: Sumber of Stabilizer Device	Load Bearing Soil Canacity:	or Assumed 1000 PS	F		
I-Beam or Main Rail Piers: Single Tiered: Double Interlocked: Size of Piers: Placement O/C: Primeter Pier Blocking Size: Placement O/C: Ridge Beam Support Blocking Size: Number: Location(s)	Footing Type: Pound in Place:	Portable:	Size and Thick	ness:	
Size of Piers: Placement O/C:	I-Beam or Main Rail Piers: Single Tiered: Double Interlocked:				
Perimeter Pier Blocking Size: Placement O/C: Ridge Beam Support Blocking Size: Number: Location(s) Ridge Beam Support Footer Size: Number: Location(s) Center Line Blocking: Number: Size: Location(s) Special Pier Blocking: Required: (Fireplace, Bay Window, Etc.) YES: NO: Matting of Multiple Units: Matting Gasket: Type Used: Fasteners: ROOFS	Size of Piers: Placement O/C:				
Matting of Multiple Units: Matting Gasket: Type Used: O/C Fasteners: ROOFS	Perimeter Pier Blocking Size:	Placement O/C:			
Matting of Multiple Units: Matting Gasket: Type Used: O/C Fasteners: ROOFS	Ridge Beam Support Blocking Size: Number: Location(s)				
Matting of Multiple Units: Matting Gasket: Type Used: O/C Fasteners: ROOFS	Ridge Beam Support Footer Size:	Number:	Location(s)	`	
Matting of Multiple Units: Matting Gasket: Type Used: O/C Fasteners: ROOFS	Center Line Blocking: Number:	Size:	Location(s)		
Matting of Multiple Units: Matting Gasket: Type Used: Fasteners: ROOFS	Special Fiel Blocking, Required, (Fire	splace, Day willidow, L	w., ilb.	110.	
Fasteners: ROOFS Type and Size: Spacing: O/C END WALLS Type and Size: Spacing: O/C FLOORS Type and Size: Spacing: O/C ANCHORS: Type 3150 Working Load: 4000 Working Load: Height of Unit: (Top of Foundation or Footer to Bottom of Frame) Number of Frame Ties: Spacing: O/C Angle of Strap: Degrees: Number of Over Roof Ties: (If Required) Number of Sidewall Anchors: Zone II Zone III Number of Centerline Anchors: Number of Stabilizer Devices:	Matting of Multiple Units: Matting G	asket: Typ	e Used:		
END WALLS Type and Size: Spacing: O/C FLOORS Type and Size: Spacing: O/C ANCHORS: Type 3150 Working Load: 4000 Working Load: Height of Unit: (Top of Foundation or Footer to Bottom of Frame) Number of Frame Ties: Spacing: O/C Angle of Strap: Degrees: Number of Over Roof Ties: (If Required) Number of Sidewall Anchors: Zone II Zone III Number of Centerline Anchors: Number of Stabilizer Devices:	Fasteners: ROOFS Type a	and Size:	Spacing:	O/C	
ANCHORS: Type and Size: Spacing: O/C ANCHORS: Type 3150 Working Load: 4000 Working Load: Height of Unit: (Top of Foundation or Footer to Bottom of Frame) Number of Frame Ties: Spacing: O/C Angle of Strap: Degrees: Number of Over Roof Ties: (If Required) Number of Sidewall Anchors: Zone II Zone III Number of Centerline Anchors: Number of Stabilizer Devices:	END WALLS Type a	and Size: S	Spacing:	O/C	
Type 3150 Working Load: 4000 Working Load: Height of Unit: (Top of Foundation or Footer to Bottom of Frame) Number of Frame Ties: Spacing: O/C Angle of Strap: Degrees: Number of Over Roof Ties: (If Required)	FLOORS Type a	ınd Size: S	Spacing:	O/C	
Height of Unit: (Top of Foundation or Footer to Bottom of Frame)	ANCHORS:				
Height of Unit: (Top of Foundation or Footer to Bottom of Frame)	T 2150 W 1' I 1	4000 W 1: I 1			
Number of Frame Ties: Spacing: O/C Angle of Strap: Degrees: Number of Over Roof Ties: (If Required) Zone II Zone III Number of Centerline Anchors: Number of Stabilizer Devices:	Height of Unit. (Top of Foundation or Footer to Pottom of Frame)				
Number of Over Roof Ties: (If Required) Number of Sidewall Anchors: Number of Centerline Anchors: Number of Stabilizer Devices: Number of Stabilizer Devices:	Number of Frame Ties: Specing: O/C Angle of Strop: Degrees:				
Number of Centerline Anchors: Number of Stabilizer Devices:	Number of Over Roof Ties: (If Doggie	nig U/C Ang	te of Suap:	Degrees.	
Number of Centerline Anchors: Number of Stabilizer Devices:	Number of Sidewall Anchora	Zone II	Zona III		
Number of Centernic Anciors. Number of Stabilizer Devices.	Number of Centerline Anchors:	Zulle II Number of Stak	Zuic III		
Vents Required for Underninning (1 SE/150 SE of Floor Area) Number:					